



•ximea



xiSPEC2

Compact hyperspectral cameras
with USB3 and PCIe interfaces



xiSPEC2 hyperspectral cameras

The smallest USB3 and PCIe hyperspectral cameras.

Facts

- Cameras with 15 up to 150 bands
- 170 fps with USB3 interface, 340 fps with PCIe
- Snapshot and linescan versions
- Smallest and lightest hyperspectral cameras available
- Low power consumption
- Rugged, without moving parts
- Each camera is spectrally calibrated

Features

- Small - fast - flexible
- Snapshot with global shutter
 - 4x4 with 15 spectral bands in the red and NIR 600-860 nm range
 - 4x4 with 16 spectral bands in the visible 460-600 nm range
 - 5x5 with 24 spectral bands in the NIR 665-960 nm range
- Multi-linescan with global shutter
 - 150 spectral bands 470-900 nm range
- Starter kit available for rapid development
- Flexible and programmable GPIO options



Hyperspectral

A Fabry-Perrot interference filter array on top of a fast CMOS sensor creates the basis for a camera design that combines hyperspectral imaging with high frame rates and a compact form factor. The obtained imagery can be interpreted to determine the chemical composition of materials.

Small & light


Simply the most compact method of retrieving hyperspectral imagery of a subject. Being small and light as well as having low power consumption makes the cameras ideal for mobile applications such as UAVs or handheld devices.

Fast



USB3.1 or PCIe interfaces allow extreme data acquisition rates. For either option, the data can be processed on the fly or saved for later analysis.

Housing examples



Standard C/CS-mount with model-specific, customized filter glass



Housed cameras with Micro-B connector






Semi housed cameras with 'FL' ribbon cable connector



PCI Express Options

All HSI cameras are compatible with xiFLY configurations and are available with PCIe interfaces



- High speed interface with compact ribbon cable connection
- Up to 340 fps
- Interface is ideal for embedded/mobile and NVIDIA Jetson installation
- Inquire with your representative for availability

Supported operating systems



Windows



Linux

macOS


Language support



Standards



Supported vision libraries



MATLAB



and many more ...

Sensors and models

Model (USB3 microB)	Sensor	Resolution	Pix. size [µm]	ADC [bits]	Sensor size / diagonal [mm]	Optical size	Fps ¹	Power typ. [W]	Spectral Bands	Spectral Range
MQ022HG-IM-LS150-VN2	IMEC CMV2K LS150	2048 x 1088 2.2 Mpix	5.5	10	11.3 x 6.0 12.7	2/3"	170	1.6	150	470-900
MQ022HG-IM-SM4X4-RN2	IMEC CMV2K-SSM4x4-RNIR	2048 x 1088 2.2 Mpix	5.5	10	11.3 x 6.0 12.7	2/3"	170	1.6	15	600-860
MQ022HG-IM-SM4X4-VIS3	IMEC CMV2K-SSM4x4-VIS	2048 x 1088 2.2 Mpix	5.5	10	11.3 x 6.0 12.7	2/3"	170	1.6	16	460-600
MQ022HG-IM-SM5X5-NIR2	IMEC CMV2K-SSM5x5-NIR	2048 x 1088 2.2 Mpix	5.5	10	11.3 x 6.0 12.7	2/3"	170	1.6	24	665-960

Notes

¹ Full resolution. RAW8 format

Sales offices

Worldwide

XIMEA GmbH

Am Mittelhafen 16
48155 Münster
Germany

Tel: +49 (251) 202 408 0

Slovakia and Czech Republic

XIMEA s.r.o

Lesna 52
900 33 Marianka
Slovakia

Tel: +421 (2) 205 104 26

America

XIMEA Corp.

8725 W 14th Ave
80215 Lakewood, CO
USA

Tel: +1 (303) 389 983 8

info@ximea.com

Further information

Please visit us at www.ximea.com for complete and up-to-date specifications. Get in touch with our teams at sales@ximea.com. We will be glad to assist!



xiSPEC2